



BROTHERS
PHARMAMACH (INDIA) PVT. LTD.

CAPSEAL 60L

Automatic Four Head LUG Cap Jar Capping Machine



The Automatic Four Head Rotary Pick and Place type Lug Capping Machine Model CAPSEAL-60L for LUG Caps. Machine Capping head and design is suitable to handle Lug Caps for Round or other shape of Glass Bottles with maximum speed of 60 Bottles per minute depending on Bottle Diameter, Bottle Height, Bottle Shape and Cap Size. Machine with Pneumatically operated Gripper type capping head system for uniform capping on bottles. Specially Machine construction in Stainless Steel finish including machine M.S. frame structure with Stainless Steel Cladding/Enclosures. The Capping Machine is ideal for application in Food, Pesticides, Cosmetic & Other Industries.

The Machine is equipped with Orientation type Cap Feeder for continues feeding of Cap for online operation on any liquid or powder filling line. Machine suitable for various sizes of Bottles and Caps with the help of change parts.



SPECIAL/OPTIONAL FEATURES :

- No Bottle - No Cap System
- No Cap - Machine Stop System
- Pneumatically operated Gripper type Capping Head
- Machine construction in Stainless Steel Finish
- In-feed and Exit Star Wheel with Overload Clutch System to avoid Bottle breakage
- Single Drive Synchronizing Total Operation of Star Wheel and Turret with Star Wheel
- Cap Feeder with Variable Speed System for feeding control of caps.
- Minimum Change Over and Setting time
- Hopper can be completely dismantle for easy cleaning
- Various safety features including Clutch system to avoid Bottle Breakage
- Single Drive synchronizing operation of Conveyor and Star Wheel
- Minimum Change over time

Other Available Models

CAPSEAL-20	CAPSEAL-40SR	CAPSEAL-120R	CAPSEAL-160R
CAPSEAL-80R	CAPSEAL-200R	CAPSEAL-240R	CAPSEAL-120SR
CAPSEAL-80L	CAPSEAL-80SR	CAPSEAL-120.MB	CAPSEAL-160SR.PNP
CAPSEAL-40R	CAPPRESS-150	CAPSEAL-80SR.PNP	CAPSEAL-240SR.PNP
CAPSEAL-120	CAP ELEVATOR	CAPSEAL-120SR.PNP	CAPSEAL-300SR.PNP
CAPSEAL-250	CAPSEAL-400	CAPPRESS-250R	CAPPRESS-160R.PNP

TECHNICAL SPECIFICATIONS

Bottle Size : Diameter 60mm to 100mm for Broad Neck and 45mm to 100mm for Narrow Neck
 Bottle Height : 75mm to 260mm* Maximum
 Lug Cap Size : 22 to 55mm*
 Electrical : 415VAC 3Phase and 220 VAC Single Phase Power Supply (50 Hz) with A.C. Drive
 Power : 3.0 Hp
 Conveyor Height : 850-900 mm
 Overall Dimensions : 3000 mm (L) x 1150 mm (W) x 2300 mm (H)
 Speed : Max. 60 Bottles per minute depending on Bottle and Cap Size

* Specification can be changed as per customers requirements

Email : sales@brothers.in
 Export : sales1@brothers.in

Phone : +91 79 40213213 / 25831346

www.brothersindia.com